



DUCT TAPE

FIXING & SEALING

DUCT TAPE is appropriate to sealing round ducts. It is particularly suitable for applications in mechanical ventilation systems.

CONSTRUCTION:

DUCT TAPE is a linnen-tape, a composition of polyethylene and plastic, provided with a natural rubber sealing coat layer. The maximal elongation is 8%.

SPECIFICATIONS

Article code:	DUCT{width}
Standard length:	50 mtr
Standard thickness:	310 microns
Standard width:	050 and 075 mm (100mm on request)
Operating temperature:	-20 °C to 75 °C
Processing temperature:	+5 °C to 30 °C
Operating pressure:	up to +1500 Pa
Standard Colour:	Grey (Other colours are available on request)



STORAGE

DUCT TAPE has a lifespan of one year if stored between 10 °C and 30 °C and the packaging is kept dry and sealed.

ADHESION

The adhesion is 0.55kg/cm if the surface is fat-free and dust-free. The ultimate tensile failure is 5.9 kg / cm.

Surfaces must be clean and free of moisture and foreign contamination; a remote trace of moisture will seriously affect adhesion.

LIABILITY:

The information contained in this brochure was current on the publication date. DEC INTERNATIONAL reserves the right to make changes in details at any time without prior notice. In order to avoid misunderstandings, any interested party is advised to contact DEC INTERNATIONAL checking for any changes in materials and/or information after this brochure was published.

PLEASE NOTICE:

The consultant is responsible for the actual installation and mounting of the product. The mentioned values with respect to temperatures are not appropriate to be used to determine the physical properties. These properties are also dependent on humidity and the temperature of the air inside and outside of the H.V.A.C. system.

TRADEMARKS:

DEC International and the DEC logo are trademarks, or registered trademarks of Dutch Environment Corporation BV in the Netherlands and/or other countries.